

F677TSVV-APD

75 Ohm Coaxial Cable

Drop Cable

CATV (ETL)

1100 CommScope Place
Hickory, NC 28603
(800) 982-1708
(828) 324-2200
Fax: (828) 324-3400
Int'l Fax: (828) 323-4989
www.commscope.com
CommScope Properties, LLC
All Rights Reserved



PRODUCT DESCRIPTION:

BONDED LAMINATED ALUMINUM TAPE, 77% BRAID, LAMINATED ALUMINUM TAPE, AMORPHOUS POLYPROPYLENE FLOODING COMPOUND (NON-FLOWING), FLAME RETARDANT PVC JACKET, MEETS NEC ARTICLE 820V RATING (ETL LISTED)

CENTER CONDUCTOR:

18 AWG COPPER-CLAD STEEL
NOMINAL DIAMETER: 0.040" (1.02 mm)

DIELECTRIC:

GAS EXPANDED POLYETHYLENE
NOMINAL DIAMETER OVER DIELECTRIC: 0.180" (4.57 mm)

SHIELD:

1ST SHIELD: LAMINATED ALUMINUM TAPE BONDED TO THE DIELECTRIC
NOMINAL DIAMETER OVER TAPE: 0.187" (4.75 mm)
2ND SHIELD: 34 AWG ALUMINUM BRAID WIRE
77% COVERAGE
3RD SHIELD: LAMINATED ALUMINUM TAPE

JACKET:

FLAME RETARDANT PVC
NOMINAL DIAMETER OVER JACKET: 0.278" (7.06 mm)
NOMINAL JACKET THICKNESS: 0.030" (0.76 mm)

CORROSION RESISTANT TREATMENT:

AMORPHOUS POLYPROPYLENE FLOODING COMPOUND

ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 +/- 3.0 Ohms
VELOCITY OF PROPAGATION: 85.0% NOMINAL
ATTENUATION: @ 68°F (20°C)



Shipping Weight (Lbs.)/1000':34 lbs.

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.58 dB	1.90 dB
55 MHz	1.60 dB	5.25 dB
83 MHz	1.95 dB	6.40 dB
187 MHz	2.85 dB	9.35 dB
211 MHz	3.05 dB	10.00 dB
250 MHz	3.30 dB	10.82 dB
300 MHz	3.55 dB	11.64 dB
350 MHz	3.85 dB	12.63 dB
400 MHz	4.15 dB	13.61 dB
450 MHz	4.40 dB	14.44 dB
500 MHz	4.66 dB	15.29 dB
550 MHz	4.90 dB	16.08 dB
600 MHz	5.10 dB	16.73 dB
750 MHz	5.65 dB	18.54 dB
865 MHz	6.10 dB	20.01 dB
1000 MHz	6.55 dB	21.49 dB