



Stream (192.168.1.46) - MTM400A Transport Stream Monitor

FileViewNavigationSettingsHelp

Connect...Interface...Standard...Configuration...Idle

Reset Tests

FlexVu™Analysis

All PIDs > Summary

All PIDs (12): Network Name: Multiplexer

	PID		Stream type	Current Bit Rate	Current(Kbps)	%	Min(kbps)	Max(Kbps)	CC
●	0 (0x0)		PID 0 (PAT)		15.040	<0.01%	13.536	15.040	0
●	1 (0x1)		PID 1 (CAT)		15.040	<0.01%	12.032	15.040	0
●	16 (0x10)		PID 16 (NIT or ...)		15.040	<0.01%	12.032	15.040	0
●	17 (0x11)		PID 17 (SDT, B...		15.040	<0.01%	12.032	15.040	0
●	34 (0x22)		PMT		15.040	<0.01%	12.032	15.040	0
●	35 (0x23)	⚙	2 (0x02) (MPEG...		1726.592	28.13%	1716.064	1737.120	0
●	36 (0x24)		4 (0x04) (MPEG...		184.992	3.01%	184.992	189.504	0
●	37 (0x25)		PMT		15.040	<0.01%	12.032	15.040	0
●	38 (0x26)	⚙	2 (0x02) (MPEG...		1726.592	28.13%	1713.056	1741.632	0
●	39 (0x27)		4 (0x04) (MPEG...		189.504	3.09%	184.992	189.504	0
✖	308 (0x134)		unknown		0.000	0	0.000	0.000	0
●	8191 (0x1FFF)		PID 8191 (Null)		2219.904	36.17%	2204.864	2245.472	0

Login:AdminTS AvailabilitySyncBit rate 6.137574 Mbps @ 188Packet Size: 188DVBNo ExtensionsInterface: ASI

StartMTM Remote User Interf...Stream (192.168.1.46...Document1 - Microsoft ...10:56 AM